

LESTER®

ALFs DÄCKIMPORT ÖDENÄS



LESTER® TIRE SPECS						
SIZE	PHOTO	WW WIDTH	CONSTRUCTION	LOAD CAPACITY	TREAD WIDTH	OVERALL DIAMETER
32x4	I, J	2 ^{1/2} "	6 PR Rayon	1000 @ 60 psi	3.20	32.75
32x4 ^{1/2}	I, J	2 ^{3/4} "	6 PR Rayon	1250 @ 65 psi	3.60	33.25
33x4	I, J	2 ^{1/2} "	6 PR Rayon	1000 @ 60 psi	3.20	33.80
33x4 ^{1/2}	I, J	2 ^{3/4} "	6 PR Rayon	1250 @ 65 psi	3.50	34.00
34x4	I, J	2 ^{1/2} "	6 PR Rayon	1000 @ 60 psi	3.20	34.25
34x4 ^{1/2}	I, J	2 ^{3/4} "	6 PR Rayon	1350 @ 65 psi	3.50	34.80
35x5	I, J	4"	8 PR Rayon	1700 @ 65 psi	4.00	36.75
36x4	I, J	2 ^{1/2} "	6 PR Rayon	1000 @ 60 psi	3.20	36.60
36x4 ^{1/2}	I, J	3"	6 PR Rayon	1350 @ 65 psi	3.45	36.75
37x5	I, J	4"	8 PR Rayon	1700 @ 65 psi	4.00	38.25
38x4 ^{1/2} CL	I	Black only	8 PR Rayon	1450 @ 70 psi	3.45	38.50
850-14	A	3"	4 Ply Poly	1740 @ 32 psi	5.20	29.10
950-14	B	2 ^{1/2} "	4 Ply Poly/6PR	2130 @ 36 psi	5.20	29.30
700-15	C	4"	4 Ply Poly/6PR	1820 @ 36 psi	5.55	29.65
820-15	D	4 1/4"	4 Ply Poly	1920 @ 32 psi	5.85	30.90
600-16	C	3 ^{7/8} "	4 Ply Poly/6PR	1500 @ 36 psi	4.40	28.40
650-16	C	4"	4 Ply Poly/6PR	1690 @ 36 psi	5.10	29.25
700-16	E	4 ^{1/2} "	4 Ply Poly/6PR	1900 @ 36 psi	5.30	30.40
750-16	F	5"	4 Ply Poly/6PR	2175 @ 36 psi	5.80	32.20
825-16	H	5 ^{3/8} "	6 Ply Poly	1760 @ 34 psi	6.50	32.00
525/550-17	H	3 ^{3/4} "	4 Ply Poly	958 @ 32 psi	4.15	28.95
600/650-17	H	4"	4 Ply Nyl/ 6PR	1320 @ 36 psi	4.50	29.25
700-17	H	4 ^{7/8} "	4 Ply Poly/6PR	1645 @ 36 psi	5.25	31.25
750-17	H	5"	4 Ply Poly/8PR	1825 @ 40 psi	5.50	33.00
525/550-18	G	3 ^{1/4} "	4 Ply Poly	1000 @ 32 psi	4.30	29.35
600/650-18	H	4"	4 Ply Poly/6PR	1375 @ 36 psi	4.50	30.50
700-18	H	4 ^{7/8} "	4 Ply Poly/6PR	1525 @ 36 psi	5.25	32.00
750-18	H	5"	4 Ply Poly/8PR	1900 @ 40 psi	5.50	33.75
475/500-19	H	3"	4 Ply Poly	895 @ 32 psi	3.70	29.80
525/550-19	H	3 ^{7/8} "	4 Ply Poly	1050 @ 32 psi	4.25	30.75
600-19	H	4"	4 Ply Poly/6PR	1255 @ 36 psi	4.50	31.50
650-19	H	4 ^{3/8} "	4 Ply Poly/8PR	1625 @ 40 psi	5.00	32.25
700-19	H	4 ^{7/8} "	4 Ply Poly/6PR	1585 @ 36 psi	5.25	32.75
750-19	H	5"	4 Ply Poly/8PR	1970 @ 40 psi	5.50	35.00
475/500-20	H	3"	4 Ply Poly	925 @ 32 psi	4.00	30.50
525/550-20	H	3 ^{7/8} "	4 Ply Poly	1075 @ 32 psi	4.13	31.50
600/650-20	H	4"	4 Ply Poly/6PR	1500 @ 36 psi	4.50	32.00
700-20	H	4 ^{5/8} "	4 Ply Poly/6PR	1700 @ 36 psi	5.00	33.50
440/450-21	H	2 ^{3/8} "	4 Ply Poly	900 @ 32 psi	3.25	30.75
525/550-21	H	3 ^{7/8} "	4 Ply Poly	1075 @ 32 psi	4.25	32.50
600-21	H	3 ^{3/4} "	4 Ply Poly/6PR	1350 @ 36 psi	4.50	32.75
700-21	H	4 ^{5/8} "	4 Ply Poly/6PR	1700 @ 36 psi	5.00	34.50
600-23	H	3 ^{3/4} "	4 Ply Poly/6PR	1350 @ 36 psi	4.50	35.00

CL=Cincher These tires are designed for vehicles manufactured prior to 1976.

TELEFON 0322-53437